




ARRANGE METHOD:



- Remark:**
- ① Cable: Cat. 6A SFTP, Stranded Bare Copper, 4Pairs Wires, 26AWG, Jacket LS0H, OD: 6.5mm.
 - ② Plug: Cat. 6A Unbreakable Shielded Type Plug with 3 Prongs, 50u", 8P8C, UL94-V2, Mating Cycle >1200.
 - ③ Packing: 1PC/PE Bag with Label.
- Testing: 100% CAT. 6A Component Test.
All materials are RoHS compliant.



CUT LINE AND ARRANGE CRITERION				CUT LINE AND ARRANGE CRITERION			
No.	Total length (mm)	no of patch cord	Cable tie (mm)	No.	Total length (mm)	no of patch cord	Cable tie (mm)
1	300	A	/	19	13000	B	C
2	500	B	/	20	14000	C	175
3	1000	/	/	21	15000		180
4	1500	175	60	22	16000		205
5	2000		70	23	17000		210
6	2500		80	24	18000		215
7	3000	185	95	25	19000		220
8	3500		100	26	20000		225
9	4000		110	27	25000	120	265
10	5000		120	28	30000		315
11	6000		130	29	40000		365
12	7000		135	30	50000		415
13	7500	135	140	31	60000		465
14	8000		145	32	70000		515
15	9000		150	33	80000		565
16	10000		165	34	90000		615
17	11000	120	170	35	100000		665
18	12000		175	36			

WIRE CONNECTION TABLE								LENGTH		MOLD NO.	
	white/ orange	white/ green	blue/ blue	white/ blue	green/ brown	white/ brown					
A1	A2	A3	A4	A5	A6	A7	A8				
B1	B2	B3	B4	B5	B6	B7	B8	(1+40)75(0)75x(10)		02-012	

DWG. NO. P6ASSB012-004			
TITLE CAT.6A S/FTP Unbreakable PATCH CORD			
UNIT mm			
SCALE 1/1	SHEET 1/1		
DRAWN DATE 2017/10/10	PROJ.	REV 1	
APPROVAL	CHECKED	DRAWN	
		CathyLi	