




ARRANGE METHOD:



- Remark:**
- ① Cable: Cat. 6A SFTP, Stranded Bare Copper, 4Pairs Wires, 26AWG, Jacket LSOH, OD: 6.5mm.
  - ② Plug: Cat. 6A Unbreakable Unshielded Type Plug with 3 Prongs, 50u", 8P8C, UL94-V2, Mating Cycle >1200.
  - ③ Packing: 1PC/PE Bag with Label.

Testing: 100% CAT. 6A Component Test.  
All materials are RoHS compliant.



CUT LINE AND ARRANGE CRITERION				CUT LINE AND ARRANGE CRITERION			
No.	Total length (mm)	no. of patch cord (mm)	Cable tie (mm)	No.	Total length (mm)	no. of patch cord (mm)	Cable tie (mm)
1	300	A	/	19	13000		175
2	500	B	/	20	14000		180
3	1000	/	/	21	15000		205
4	1500	175	60	22	16000		210
5	2000		70	23	17000		215
6	2500		75	24	18000		220
7	3000	185	80	25	19000		225
8	3500		95	26	20000		235
9	4000		100	27	25000	120	265
10	5000		110	28	30000		315
11	6000		120	29	40000		365
12	7000		130	30	50000		415
13	7500		135	31	60000		465
14	8000	135	140	32	70000		515
15	9000		145	33	80000		565
16	10000		150	34	90000		615
17	11000		155	35	100000		665
18	12000	120	170	36			

WIRE CONNECTION TABLE								LENGTH		MOLD NO.	
	white/ orange	white/ green	blue/ blue	white/ blue	green/ brown	white/ brown					
A1	A2	A3	A4	A5	A6	A7	A8				
B1	B2	B3	B4	B5	B6	B7	B8	(1+80)24(0)743(0)		02-012	

DWG. NO.

P6AUTTB012-003

TITLE

CAT.6A UTP Unbreakable PATCH CORD

UNIT	SCALE	SHEET
mm	1/1	1/1
DRAWN DATE	PROJ.	REV
2017/10/10		1
APPROVAL	CHECKED	DRAWN
		CathyLi