



ARRANGE METHOD:



Remark:
 ① Cable: Cat.6 UTP, Stranded Bare Copper, 4Pairs Wires, 30AWG, Jacket PVC, OD: 1.6*6.7mm, Flat Cable.
 ② Plug: Cat.6 Unshielded Type Plug with 3 Prongs, 50u", 8P8C, UL94-V2, Mating Cycle >1200.
 ③ Packing: IPC/PE Bag with Label.
 Testing: 100% Component Test.
 All materials are RoHS compliant.

ROHS

RELEASED
 2017. 10. 11
 R&D

CUT LINE AND ARRANGE CRITERION				CUT LINE AND ARRANGE CRITERION			
No.	Total Length (MM)	no. of patch cord	Cable Tie (MM)	No.	Total Length (MM)	no. of patch cord	Cable Tie (MM)
1	300	A	/	19	13000	A	C
2	500	/	/	20	14000	/	175
3	1000	/	/	21	15000	/	160
4	1500	175	60	22	16000	/	205
5	2000	/	70	23	17000	/	210
6	2500	/	75	24	18000	/	215
7	3000	195	80	25	19000	/	220
8	3500	/	95	26	20000	/	225
9	4000	/	100	27	25000	/	235
10	5000	/	110	28	30000	/	265
11	6000	/	120	29	40000	/	315
12	7000	/	130	30	50000	/	365
13	7500	135	135	31	60000	/	415
14	8000	/	140	32	70000	/	465
15	9000	/	145	33	80000	/	515
16	10000	/	150	34	90000	/	565
17	11000	165	155	35	100000	/	615
18	12000	170	165	36	/	/	665

WIRE CONNECTION TABLE								LENGTH		MOLD NO.	
white/ orange	white/ green	blue/ blue	white/ blue	green/ blue	white/ brown	white/ brown					
A1	A2	A3	A4	A5	A6	A7	A8	(4*80)(4*90)(4*100)	02-075		
B1	B2	B3	B4	B5	B6	B7	B8				

DWG. NO. P60UTTB075-001			
TITLE CAT.6 UTP FLAT PATCH CORD			
UNIT mm	SCALE 1/1	SHEET 1/1	
DRAWN DATE 2017/10/11	PROJ. 	REV 1	DRAWN CathyLi
APPROVAL Carine	CHECKED Wuming		